

# Physics Notes Class 11 CHAPTER 11 THERMAL PROPERTIES OF MATTER

The branch dealing with measurement of temperature is called thermometry and the devices used to measure temperature are called thermometers.

## Heat

Heat is a form of energy called thermal energy which flows from a higher temperature body to a lower temperature body when they are placed in contact.

Heat or thermal energy of a body is the sum of kinetic energies of all its constituent particles, on account of translational, vibrational and rotational motion.

The SI unit of heat energy is joule (J).

The practical unit of heat energy is calorie.

$$1 \text{ cal} = 4.18 \text{ J}$$

1 calorie is the quantity of heat required to raise the temperature of 1 g of water by 1°C.

Mechanical energy or work (W) can be converted into heat (Q) by  $1 \text{ W} = JQ$

where J = Joule's mechanical equivalent of heat.

J is a conversion factor (not a physical quantity) and its value is 4.186 J/cal.

## Temperature

Temperature of a body is the degree of hotness or coldness of the body. A device which is used to measure the temperature, is called a thermometer.

Highest possible temperature achieved in laboratory is about 10<sup>8</sup> while lowest possible temperature attained is 10<sup>-8</sup> K.

Branch of Physics dealing with production and measurement temperature close to 0 K is known as cryogenics, while that dealing with the measurement of very high temperature is called pyrometry. Temperature of the core of the sun is 10<sup>7</sup> K while that of its surface 6000 K.

NTP or STP implies 273.15 K (0°C = 32°F).

## Different Scale of Temperature

1. **Celsius Scale** In this scale of temperature, the melting point ice is taken as  $0^{\circ}\text{C}$  and the boiling point of water as  $100^{\circ}\text{C}$  and space between these two points is divided into 100 equal parts
2. **Fahrenheit Scale** In this scale of temperature, the melt point of ice is taken as  $32^{\circ}\text{F}$  and the boiling point of water as 211 and the space between these two points is divided into 180 equal parts.
3. **Kelvin Scale** In this scale of temperature, the melting pouxl ice is taken as 273 K and the boiling point of water as 373 K the space between these two points is divided into 100 equal pss

### Relation between Different Scales of Temperatures

$$\frac{C}{100} = \frac{F - 32}{180} = \frac{K - 273}{100} = \frac{R}{80}$$

### Thermometric Property

The property of an object which changes with temperature, is call thermometric property. Different thermometric properties thermometers have been given below

#### (i) Pressure of a Gas at Constant Volume

$$\frac{P_1}{T_1} = \frac{P_2}{T_2}$$

and

$$P_t = P_0 \left( 1 + \frac{t}{273} \right)$$

$$t = \left( \frac{P_t - P_0}{P_{100} - P_0} \times 100 \right)^{\circ}\text{C}$$

where  $p$ ,  $p_{100}$ . and  $p_t$ , are pressure of a gas at constant volume  $0^{\circ}\text{C}$ ,  $100^{\circ}\text{C}$  and  $t^{\circ}\text{C}$ .

A constant volume gas thermometer can measure tempera from  $-200^{\circ}\text{C}$  to  $500^{\circ}\text{C}$ .

#### (ii) Electrical Resistance of Metals

$$R_t = R_0(1 + \alpha t + \beta t^2)$$

where  $\alpha$  and  $\beta$  are constants for a metal.

As  $\beta$  is too small therefore we can take

$$R_t = R_0(1 + \alpha t)$$

where,  $\alpha$  = temperature coefficient of resistance and  $R_0$  and  $R_t$ , are electrical resistances at  $0^\circ\text{C}$  and  $t^\circ\text{C}$ .

$$\alpha = \frac{R_2 - R_1}{R_1 t_2 - R_2 t_1}$$

where  $R_1$  and  $R_2$  are electrical resistances at temperatures  $t_1$  and  $t_2$ .

$$t = \frac{R_t - R_0}{R_{100} - R_0} \times 100^\circ\text{C}$$

where  $R_{100}$  is the resistance at  $100^\circ\text{C}$ .

Platinum resistance thermometer can measure temperature from  $-200^\circ\text{C}$  to  $1200^\circ\text{C}$ .

### (iii) Length of Mercury Column in a Capillary Tube

$$l_t = l_0(1 + \alpha t)$$

where  $\alpha$  = coefficient of linear expansion and  $l_0$ ,  $l_t$  are lengths of mercury column at  $0^\circ\text{C}$  and  $t^\circ\text{C}$ .

### Thermo Electro Motive Force

When two junctions of a thermocouple are kept at different temperatures, then a thermo-emf is produced between the junctions, which changes with temperature difference between the junctions. Thermo-emf

$$E = at + bt^2$$

where  $a$  and  $b$  are constants for the pair of metals.

Unknown temperature of hot junction when cold junction is at  $0^\circ\text{C}$ .

$$t = \left( \frac{E_t}{E_{100}} \times 100 \right)^\circ\text{C}$$

Where  $E_{100}$  is the thermo-emf when hot junction is at  $100^\circ\text{C}$ .

A thermo-couple thermometer can measure temperature from  $-200^\circ\text{C}$  to  $1600^\circ\text{C}$ .

### Thermal Equilibrium

When there is no transfer of heat between two bodies in contact, the the bodies are called in thermal equilibrium.

## Zeroth Law of Thermodynamics

If two bodies A and B are separately in thermal equilibrium with a third body C, then bodies A and B will be in thermal equilibrium with each other.

## Triple Point of Water

The values of pressure and temperature at which water coexists in equilibrium in all three states of matter, i.e., ice, water and vapour called triple point of water.

Triple point of water is 273 K temperature and 0.46 cm of mercury pressure.

## Specific Heat

The amount of heat required to raise the temperature of unit mass of the substance through  $1^\circ\text{C}$  is called its specific heat.

It is denoted by  $c$  or  $s$ .

Its SI unit is joule/kilogram- $^\circ\text{C}$  ( $\text{J}/\text{kg}\cdot^\circ\text{C}$ ). Its dimensions are  $[\text{L}^2\text{T}^{-2}\theta^{-1}]$ .

The specific heat of water is  $4200 \text{ J kg}^{-1}\text{C}^{-1}$  or  $1 \text{ cal g}^{-1} \text{ C}^{-1}$ , which is high compared with most other substances.

## Gases have two types of specific heat

1. The specific heat capacity at constant volume ( $C_V$ ).
2. The specific heat capacity at constant pressure ( $C_P$ ).

Specific heat at constant pressure ( $C_P$ ) is greater than specific heat at constant volume ( $C_V$ ), i.e.,  $C_P > C_V$ .

For molar specific heats  $C_P - C_V = R$   
where  $R$  = gas constant and this relation is called Mayer's formula.

The ratio of two principal specific heats of a gas is represented by  $\gamma$ .

$$\gamma = \frac{C_P}{C_V}$$

The value of  $\gamma$  depends on the atomicity of the gas.

Amount of heat energy required to change the temperature of any substance is given by

$$Q = mc\Delta t$$

- where,  $m$  = mass of the substance,
- $c$  = specific heat of the substance and
- $\Delta t$  = change in temperature.

### **Thermal (Heat) Capacity**

Heat capacity of any body is equal to the amount of heat energy required to increase its temperature through  $1^\circ\text{C}$ .

Heat capacity =  $mc$

where  $c$  = specific heat of the substance of the body and  $m$  = mass of the body.

Its SI unit is joule/kelvin (J/K).

### **Water Equivalent**

It is the quantity of water whose thermal capacity is same as the heat capacity of the body. It is denoted by  $W$ .

$W = mc$  = heat capacity of the body.

### **Latent Heat**

The heat energy absorbed or released at constant temperature per unit mass for change of state is called latent heat.

Heat energy absorbed or released during change of state is given by

$$Q = mL$$

where  $m$  = mass of the substance and  $L$  = latent heat.

Its unit is cal/g or J/kg and its dimension is  $[\text{L}^2\text{T}^{-2}]$ .

For water at its normal boiling point or condensation temperature ( $100^\circ\text{C}$ ), the latent heat of vaporisation is

$$\begin{aligned} L &= 540 \text{ cal/g} \\ &= 40.8 \text{ kJ/mol} \\ &= 2260 \text{ kJ/kg} \end{aligned}$$

For water at its normal freezing temperature or melting point ( $0^\circ\text{C}$ ), the latent heat of fusion is

$$\begin{aligned} L &= 80 \text{ cal/g} = 60 \text{ kJ/mol} \\ &= 336 \text{ kJ/kg} \end{aligned}$$

It is more painful to get burnt by steam rather than by boiling water as  $100^{\circ}\text{C}$  gets converted to water at  $100^{\circ}\text{C}$ , then it gives out 536 heat. So, it is clear that steam at  $100^{\circ}\text{C}$  has more heat than water at  $100^{\circ}\text{C}$  (i.e., boiling of water).

After snow falls, the temperature of the atmosphere becomes very low. This is because the snow absorbs the heat from the atmosphere to melt. So, in the mountains, when snow falls, one does not feel too hot but when ice melts, he feels too cold.

There is more shivering effect of ice cream on teeth as compared to that of water (obtained from ice). This is because when ice cream melts, it absorbs large amount of heat from teeth.

### **Melting**

Conversion of solid into liquid state at constant temperature is melting.

### **Evaporation**

Conversion of liquid into vapour at all temperatures (even below boiling point) is called evaporation.

### **Boiling**

When a liquid is heated gradually, at a particular temperature saturated vapour pressure of the liquid becomes equal to atmospheric pressure, now bubbles of vapour rise to the surface of the liquid. This process is called boiling of the liquid.

The temperature at which a liquid boils, is called boiling point. The boiling point of water increases with increase in pressure and decreases with decrease in pressure.

### **Sublimation**

The conversion of a solid into vapour state is called sublimation.

### **Hoar Frost**

The conversion of vapours into solid state is called hoar frost.

### **Calorimetry**

This is the branch of heat transfer that deals with the measurement of heat. The heat is usually measured in calories or kilocalories.

### **Principle of Calorimetry**

When a hot body is mixed with a cold body, then heat lost by the hot body is equal to the heat gained by the cold body.

Heat lost = Heat gain

### **Thermal Expansion**

Increase in size on heating is called thermal expansion. There are three types of thermal expansion.

1. Expansion of solids
2. Expansion of liquids
3. Expansion of gases

### **Expansion of Solids**

Three types of expansion -takes place in solid.

**Linear Expansion** Expansion in length on heating is called linear expansion.

Increase in length

$$l_2 = l_1(1 + \alpha \Delta t)$$

where,  $l_1$  and  $l_2$  are initial and final lengths,  $\Delta t$  = change in temperature and  $\alpha$  = coefficient of linear expansion.

Coefficient of linear expansion

$$\alpha = (\Delta l / l * \Delta t)$$

where  $l$  = real length and  $\Delta l$  = change in length and

$\Delta t$  = change in temperature.

**Superficial Expansion** Expansion in area on heating is called superficial expansion.

Increase in area  $A_2 = A_1(1 + \beta \Delta t)$

where,  $A_1$  and  $A_2$  are initial and final areas and  $\beta$  is a coefficient of superficial expansion.

Coefficient of superficial expansion

$$\beta = (\Delta A / A * \Delta t)$$

where.  $A$  = area,  $\Delta A$  = change in area and  $\Delta t$  = change in temperature.

**Cubical Expansion** Expansion in volume on heating is called cubical expansion.

Increase in volume  $V_2 = V_1(1 + \gamma \Delta t)$

where  $V_1$  and  $V_2$  are initial and final volumes and  $\gamma$  is a coefficient of cubical expansion.

Coefficient of cubical expansion

$$\gamma = \frac{\Delta V}{V \times \Delta t}$$

where  $V$  = real volume,  $\Delta V$  = change in volume and  $\Delta t$  = change in temperature.

Relation between coefficients of linear, superficial and cubical expansions

$$\beta = 2\alpha \text{ and } \gamma = 3\alpha$$

$$\text{Or } \alpha:\beta:\gamma = 1:2:3$$

## 2. Expansion of Liquids

In liquids only expansion in volume takes place on heating.

(i) Apparent Expansion of Liquids When expansion of the container containing liquid, on heating is not taken into account then observed expansion is called apparent expansion of liquids.

Coefficient of apparent expansion of a liquid

$$(\gamma_a) = \frac{\text{apparent increase in volume}}{\text{original volume} \times \text{rise in temperature}}$$

(ii) Real Expansion of Liquids When expansion of the container, containing liquid, on heating is also taken into account, then observed expansion is called real expansion of liquids.

Coefficient of real expansion of a liquid

$$(\gamma_r) = \frac{\text{real increase in volume}}{\text{original volume} \times \text{rise in temperature}}$$

Both,  $\gamma_r$ , and  $\gamma_a$  are measured in  $^{\circ}\text{C}^{-1}$ .

We can show that  $\gamma_r = \gamma_a + \gamma_g$

where,  $\gamma_r$ , and  $\gamma_a$  are coefficient of real and apparent expansion of liquids and  $\gamma_g$  is coefficient of cubical expansion of the container.

## Anomalous Expansion of Water

When temperature of water is increased from  $0^{\circ}\text{C}$ , then its vol decreases upto  $4^{\circ}\text{C}$ , becomes minimum at  $4^{\circ}\text{C}$  and then increases. behaviour of water around  $4^{\circ}\text{C}$  is called, anomalous expansion water.

## 3. Expansion of Gases

There are two types of coefficient of expansion in gases

(i) Volume Coefficient ( $\gamma_v$ ) At constant pressure, the change in volume per unit volume per degree celsius is called volume coefficient.

$$\gamma_V = \frac{V_2 - V_1}{V_0 (t_2 - t_1)}$$

where  $V_0$ ,  $V_1$ , and  $V_2$  are volumes of the gas at  $0^\circ\text{C}$ ,  $t_1^\circ\text{C}$  and  $t_2^\circ\text{C}$ .

(ii) Pressure Coefficient ( $\gamma_p$ ) At constant volume, the change in pressure per unit pressure per degree celsius is called pressure coefficient.

$$\gamma_P = \frac{p_2 - p_1}{p_0 (t_2 - t_1)}$$

where  $p_0$ ,  $p_1$  and  $p_2$  are pressure of the gas at  $0^\circ\text{C}$ ,  $t_1^\circ\text{C}$  and  $t_2^\circ\text{C}$ .

### Practical Applications of Expansion

1. When rails are laid down on the ground, space is left between the end of two rails.
2. The transmission cables are not tightly fixed to the poles.
3. The iron rim to be put on a cart wheel is always of slightly smaller diameter than that of wheel.
4. A glass stopper jammed in the neck of a glass bottle can be taken out by warming the neck of the bottles.

### Important Points

- Due to increment in its time period a pendulum clock becomes slow in summer and will lose time.
- Loss of time in a time period  $\Delta T = (1/2)\alpha \Delta\theta T$   
 $\therefore$  Loss of time in any given time interval  $t$  can be given by  
 $\Delta T = (1/2)\alpha \Delta\theta t$
- At some higher temperature a scale will expand and scale reading will be lesser than true values, so that  
 true value = scale reading  $(1 + \alpha \Delta t)$   
 Here,  $\Delta t$  is the temperature difference.
- However, at lower temperature scale reading will be more or true value will be less.